
DDispatcher

Deep Modeling

Nov 20, 2021

CONTENTS:

1	Install DPDispatcher	3
2	Getting Started	5
3	Machine parameters	9
4	Resources parameters	13
5	Task parameters	17
6	DPDispatcher API	19
6.1	dpdispatcher package	19
7	Indices and tables	49
	Python Module Index	51
	Index	53

DPPDispatcher is a Python package used to generate HPC (High Performance Computing) scheduler systems (Slurm/PBS/LSF/dpcloudserver) jobs input scripts and submit these scripts to HPC systems and poke until they finish.

DPPDispatcher will monitor (poke) until these jobs finish and download the results files (if these jobs is running on remote systems connected by SSH).

**CHAPTER
ONE**

INSTALL DPDISPATCHER

DPDispatcher can installed by pip:

```
pip install dpdispatcher
```

CHAPTER
TWO

GETTING STARTED

DPDispatcher provides the following classes:

- Task class, which represents a command to be run on batch job system, as well as the essential files need by the command.
- Submission class, which represents a collection of jobs defined by the HPC system. And there may be common files to be uploaded by them. DPDispatcher will create and submit these jobs when a `Submission` instance execute `run_submission` method. This method will poke until the jobs finish and return.
- Job class, a class used by `Submission` class, which represents a job on the HPC system. `Submission` will generate jobs' submitting scripts used by HPC systems automatically with the Task and Resources
- Resources class, which represents the computing resources for each job within a `Submission`.

You can use DPDispatcher in a Python script to submit five tasks:

```
from dpdispatcher import Machine, Resources, Task, Submission

machine = Machine.load_from_json('machine.json')
resources = Resources.load_from_json('resources.json')

task0 = Task.load_from_json('task.json')

task1 = Task(command='cat example.txt', task_work_path='dir1/', forward_files=['example.
˓→txt'], backward_files=['out.txt'], outlog='out.txt')
task2 = Task(command='cat example.txt', task_work_path='dir2/', forward_files=['example.
˓→txt'], backward_files=['out.txt'], outlog='out.txt')
task3 = Task(command='cat example.txt', task_work_path='dir3/', forward_files=['example.
˓→txt'], backward_files=['out.txt'], outlog='out.txt')
task4 = Task(command='cat example.txt', task_work_path='dir4/', forward_files=['example.
˓→txt'], backward_files=['out.txt'], outlog='out.txt')

task_list = [task0, task1, task2, task3, task4]

submission = Submission(work_base='lammps_md_300K_5GPa/',
    machine=machine,
    resources=resources,
    task_list=task_list,
    forward_common_files=['graph.pb'],
    backward_common_files=[]
)
submission.run_submission()
```

DPDispatcher

where machine.json is

```
{  
    "batch_type": "Slurm",  
    "context_type": "SSHContext",  
    "local_root" : "/home/user123/workplace/22_new_project/",  
    "remote_root": "/home/user123/dpdispatcher_work_dir/",  
    "remote_profile": {  
        "hostname": "39.106.xx.xxx",  
        "username": "user123",  
        "port": 22,  
        "timeout": 10  
    }  
}
```

resources.json is

```
{  
    "number_node": 1,  
    "cpu_per_node": 4,  
    "gpu_per_node": 1,  
    "queue_name": "GPUV100",  
    "group_size": 5  
}
```

and task.json is

```
{  
    "command": "lmp -i input.lammps",  
    "task_work_path": "bct-0/",  
    "forward_files": [  
        "conf.lmp",  
        "input.lammps"  
    ],  
    "backward_files": [  
        "log.lammps"  
    ],  
    "outlog": "log",  
    "errlog": "err",  
}
```

You may also submit mutiple GPU jobs: complex resources example

```
resources = Resources(  
    number_node=1,  
    cpu_per_node=4,  
    gpu_per_node=2,  
    queue_name="GPU_2080Ti",  
    group_size=4,  
    custom_flags=[  
        "#SBATCH --nice=100",  
        "#SBATCH --time=24:00:00"  
    ],  
    strategy={
```

(continues on next page)

(continued from previous page)

```
# used when you want to add CUDA_VISIBLE_DEVICES automatically
"if_cuda_multi_devices": True
},
para_deg=1,
# will unload these modules before running tasks
module_unload_list=["singularity"],
# will load these modules before running tasks
module_list=["singularity/3.0.0"],
# will source the environment files before running tasks
source_list=["./slurm_test.env"],
# the envs option is used to export environment variables
# And it will generate a line like below.
# export DP_DISPATCHER_EXPORT=test_foo_bar_baz
envs={"DP_DISPATCHER_EXPORT": "test_foo_bar_baz"},  
()
```

The details of parameters can be found in [Machine Parameters](#), [Resources Parameters](#), and [Task Parameters](#).

MACHINE PARAMETERS

machine:

type: dict
argument path: machine

batch_type:

type: str
argument path: machine/batch_type

The batch job system type. Option: Torque, DpCloudServer, DistributedShell, Shell, LSF, PBS, Slurm

local_root:

type: str
argument path: machine/local_root

The dir where the tasks and relating files locate. Typically the project dir.

remote_root:

type: str, optional
argument path: machine/remote_root

The dir where the tasks are executed on the remote machine. Only needed when context is not lazy-local.

clean_asynchronously:

type: bool, optional, default: False
argument path: machine/clean_asynchronously

Clean the remote directory asynchronously after the job finishes.

Depending on the value of *context_type*, different sub args are accepted.

context_type:

type: str (flag key)
argument path: machine/context_type
possible choices: DpCloudServerContext, SSHContext, HDFSContext, LazyLocalContext, LocalContext

The connection used to remote machine. Option: LocalContext, LazyLocalContext, HDFSContext, DpCloudServerContext, SSHContext

When *context_type* is set to DpCloudServerContext (or its aliases dpcloudservercontext, DpCloudServer, dpcloudserver):

remote_profile:

type: dict

argument path: `machine[DpCloudServerContext]/remote_profile`

The information used to maintain the connection with remote machine.

email:

type: `str`

argument path: `machine[DpCloudServerContext]/remote_profile/email`

Email

password:

type: `str`

argument path: `machine[DpCloudServerContext]/remote_profile/password`

Password

program_id:

type: `int`

argument path: `machine[DpCloudServerContext]/remote_profile/program_id`

Program ID

input_data:

type: `dict`

argument path: `machine[DpCloudServerContext]/remote_profile/input_data`

Configuration of job

job_name:

type: `str`, optional

argument path:

`machine[DpCloudServerContext]/remote_profile/input_data/job_name`

Job name

image_name:

type: `str`, optional

argument path:

`machine[DpCloudServerContext]/remote_profile/input_data/image_name`

Name of the image which run the job, optional when platform is not ali/oss.

disk_size:

type: `str`, optional

argument path:

`machine[DpCloudServerContext]/remote_profile/input_data/disk_size`

disk size (GB), optional when platform is not ali/oss.

scass_type:

type: `str`

argument path:

`machine[DpCloudServerContext]/remote_profile/input_data/scass_type`

machine configuration.

platform:

type: str
argument path:
`machine[DpCloudServerContext]/remote_profile/input_data/platform`
Job run in which platform.

log_file:

type: str, optional
argument path:
`machine[DpCloudServerContext]/remote_profile/input_data/log_file`
location of log file.

checkpoint_files:

type: list | str, optional
argument path:
`machine[DpCloudServerContext]/remote_profile/input_data/checkpoint_files`
location of checkpoint files when it is list type. record file changes when it is string value ‘sync_files’

checkpoint_time:

type: int, optional, default: 15
argument path:
`machine[DpCloudServerContext]/remote_profile/input_data/checkpoint_time`
interval of checkpoint data been stored minimum 15.

backward_files:

type: list, optional
argument path:
`machine[DpCloudServerContext]/remote_profile/input_data/backward_files`
which files to be uploaded to remote resources. Upload all the files when it is None or empty.

When `context_type` is set to `SSHContext` (or its aliases `sshcontext`, `SSH`, `ssh`):

remote_profile:

type: dict
argument path: `machine[SSHContext]/remote_profile`

The information used to maintain the connection with remote machine.

hostname:

type: str
argument path: `machine[SSHContext]/remote_profile/hostname`
hostname or ip of ssh connection.

username:

type: str
argument path: `machine[SSHContext]/remote_profile/username`
username of target linux system

password:

type: str, optional

argument path: `machine[SSHContext]/remote_profile/password`
password of linux system

port:

type: `int`, optional, default: 22
argument path: `machine[SSHContext]/remote_profile/port`
ssh connection port.

key_filename:

type: `NoneType | str`, optional, default: `None`
argument path: `machine[SSHContext]/remote_profile/key_filename`
key filename used by ssh connection. If left `None`, find key in `~/.ssh` or use password for login

passphrase:

type: `NoneType | str`, optional, default: `None`
argument path: `machine[SSHContext]/remote_profile/passphrase`
passphrase of key used by ssh connection

timeout:

type: `int`, optional, default: 10
argument path: `machine[SSHContext]/remote_profile/timeout`
timeout of ssh connection

totp_secret:

type: `NoneType | str`, optional, default: `None`
argument path: `machine[SSHContext]/remote_profile/totp_secret`
Time-based one time password secret. It should be a base32-encoded string extracted from the 2D code.

When `context_type` is set to `HDFSContext` (or its aliases `hdfscontext`, `HDFS`, `hdfs`):

remote_profile:

type: `dict`, optional
argument path: `machine[HDFSContext]/remote_profile`

The information used to maintain the connection with remote machine. This field is empty for this context.

When `context_type` is set to `LazyLocalContext` (or its aliases `lazylocalcontext`, `LazyLocal`, `lazylocal`):

remote_profile:

type: `dict`, optional
argument path: `machine[LazyLocalContext]/remote_profile`

The information used to maintain the connection with remote machine. This field is empty for this context.

When `context_type` is set to `LocalContext` (or its aliases `localcontext`, `Local`, `local`):

remote_profile:

type: `dict`, optional
argument path: `machine[LocalContext]/remote_profile`

The information used to maintain the connection with remote machine. This field is empty for this context.

RESOURCES PARAMETERS

resources:

type: dict
argument path: resources

number_node:

type: int
argument path: resources/number_node

The number of node need for each *job*

cpu_per_node:

type: int
argument path: resources/cpu_per_node
cpu numbers of each node assigned to each job.

gpu_per_node:

type: int
argument path: resources/gpu_per_node
gpu numbers of each node assigned to each job.

queue_name:

type: str
argument path: resources/queue_name
The queue name of batch job scheduler system.

group_size:

type: int
argument path: resources/group_size
The number of *tasks* in a *job*.

custom_flags:

type: list, optional
argument path: resources/custom_flags
The extra lines pass to job submitting script header

strategy:

type: dict, optional

argument path: `resources/strategy`
strategies we use to generation job submitting scripts.

if_cuda_multi_devices:

type: bool, optional, default: True
argument path: `resources/strategy/if_cuda_multi_devices`

para_deg:

type: int, optional, default: 1
argument path: `resources/para_deg`
Decide how many tasks will be run in parallel.

source_list:

type: list, optional, default: []
argument path: `resources/source_list`
The env file to be sourced before the command execution.

module_unload_list:

type: list, optional, default: []
argument path: `resources/module_unload_list`
The modules to be unloaded on HPC system before submitting jobs

module_list:

type: list, optional, default: []
argument path: `resources/module_list`
The modules to be loaded on HPC system before submitting jobs

envs:

type: dict, optional, default: {}
argument path: `resources/envs`
The environment variables to be exported on before submitting jobs

Depending on the value of `batch_type`, different sub args are accepted.

batch_type:

type: str (flag key)
argument path: `resources/batch_type`
possible choices: Shell, Torque, Slurm, PBS, DpCloudServer, LSF, DistributedShell
The batch job system type loaded from machine/`batch_type`.

When `batch_type` is set to `Shell` (or its alias `shell`):

kwargs:

type: dict, optional
argument path: `resources[Shell]/kwargs`
This field is empty for this batch.

When `batch_type` is set to `Torque` (or its alias `torque`):

kwargs:

type: dict, optional
argument path: resources[Torque]/kwargs

This field is empty for this batch.

When *batch_type* is set to Slurm (or its alias slurm):

kwargs:

type: dict, optional
argument path: resources[Slurm]/kwargs

Extra arguments.

custom_gpu_line:

type: NoneType | str, optional, default: None
argument path: resources[Slurm]/kwargs/custom_gpu_line
Custom GPU configuration, starting with #SBATCH

When *batch_type* is set to PBS (or its alias pbs):

kwargs:

type: dict, optional
argument path: resources[PBS]/kwargs

This field is empty for this batch.

When *batch_type* is set to DpCloudServer (or its alias dpcloudserver):

kwargs:

type: dict, optional
argument path: resources[DpCloudServer]/kwargs
This field is empty for this batch.

When *batch_type* is set to LSF (or its alias lsf):

kwargs:

type: dict
argument path: resources[LSF]/kwargs
Extra arguments.

gpu_usage:

type: bool, optional, default: False
argument path: resources[LSF]/kwargs/gpu_usage
Choosing if GPU is used in the calculation step.

gpu_new_syntax:

type: bool, optional, default: False
argument path: resources[LSF]/kwargs/gpu_new_syntax

For LSF >= 10.1.0.3, new option -gpu for #BSUB could be used. If False, and old syntax would be used.

gpu_exclusive:

type: bool, optional, default: True
argument path: resources[LSF]/kwargs/gpu_exclusive

Only take effect when new syntax enabled. Control whether submit tasks in exclusive way for GPU.

custom_gpu_line:

type: `NoneType | str`, optional, default: `None`

argument path: `resources[LSF]/kwargs/custom_gpu_line`

Custom GPU configuration, starting with #BSUB

When `batch_type` is set to `DistributedShell` (or its alias `distributedshell`):

kwargs:

type: `dict`, optional

argument path: `resources[DistributedShell]/kwargs`

This field is empty for this batch.

TASK PARAMETERS

task:

type: dict

argument path: task

command:

type: str

argument path: task/command

A command to be executed of this task. The expected return code is 0.

task_work_path:

type: str

argument path: task/task_work_path

The dir where the command to be executed.

forward_files:

type: list

argument path: task/forward_files

The files to be uploaded in task_work_path before the task executed.

backward_files:

type: list

argument path: task/backward_files

The files to be download to local_root in task_work_path after the task finished

outlog:

type: NoneType | str

argument path: task/outlog

The out log file name. redirect from stdout

errlog:

type: NoneType | str

argument path: task/errlog

The err log file name. redirect from stderr

DPDISPATCHER API

6.1 dpdispatcher package

`dpdispatcher.info()`

6.1.1 Subpackages

`dpdispatcher.dpcloudserver package`

Submodules

`dpdispatcher.dpcloudserver.api module`

```
class dpdispatcher.dpcloudserver.api.API(email, password)
    Bases: object
```

Methods

<code>download</code>	
<code>download_from_url</code>	
<code>get</code>	
<code>get_jobs</code>	
<code>get_tasks</code>	
<code>get_tasks_v2</code>	
<code>get_tasks_v2_list</code>	
<code>job_create</code>	
<code>job_create_v2</code>	
<code>post</code>	
<code>refresh_token</code>	
<code>upload</code>	

`download(oss_file, save_file, endpoint, bucket_name)`

`download_from_url(url, save_file)`

DPDispatcher

```
get(url, params, retry=0)

get_jobs(page=1, per_page=10)

get_tasks(job_id, page=1, per_page=10)

get_tasks_v2(job_id, group_id, page=1, per_page=10)

get_tasks_v2_list(group_id, per_page=30)

job_create(job_type, oss_path, input_data, program_id=None)

job_create_v2(job_type, oss_path, input_data, program_id=None, group_id=None)

post(url, params, retry=0)

refresh_token()

upload(oss_task_zip, zip_task_file, endpoint, bucket_name)
```

dpdispatcher.dpcloudserver.config module

dpdispatcher.dpcloudserver.retcodes module

```
class dpdispatcher.dpcloudserver.retcodes.RETCODE
    Bases: object

    DATAERR = '2002'
    DBERR = '2000'
    IOERR = '2003'
    NODATA = '2300'
    OK = '0000'
    PARAMERR = '2101'
    PWDERR = '2104'
    REQERR = '2200'
    ROLEERR = '2103'
    THIRDERR = '2001'
    TOKENINVALID = '2100'
    UNDERDEBUG = '2301'
    UNKNOWNERR = '2400'
    USERERR = '2102'
```

```
VERIFYERR = '2105'
```

dpp dispatcher.dpcloudserver.temp_test module

dpp dispatcher.dpcloudserver.zip_file module

```
dpp dispatcher.dpcloudserver.zip_file.unzip_file(zip_file, out_dir='./')
```

```
dpp dispatcher.dpcloudserver.zip_file.zip_file_list(root_path, zip_filename, file_list=[])
```

6.1.2 Submodules

6.1.3 dpp dispatcher.JobStatus module

```
class dpp dispatcher.JobStatus.JobStatus(value)
```

Bases: `enum.IntEnum`

An enumeration.

`completing` = 6

`finished` = 5

`running` = 3

`terminated` = 4

`unknown` = 100

`unsubmitted` = 1

`waiting` = 2

6.1.4 dpp dispatcher.base_context module

```
class dpp dispatcher.base_contextBaseContext(*args, **kwargs)
```

Bases: `object`

Methods

<code>machine_arginfo()</code>	Generate the machine arginfo.
<code>machine_subfields()</code>	Generate the machine subfields.

bind_submission	
check_finish	
clean	
download	
kill	
load_from_dict	
read_file	
upload	
write_file	

bind_submission(*submission*)

check_finish(*proc*)

clean()

download(*submission*, *check_exists=False*, *mark_failure=True*, *back_error=False*)

kill(*proc*)

classmethod load_from_dict(*context_dict*)

classmethod machine_arginfo() → dargs.dargs.Argument
Generate the machine arginfo.

Returns

Argument machine arginfo

classmethod machine_subfields() → List[dargs.dargs.Argument]
Generate the machine subfields.

Returns

list[Argument] machine subfields

options = {'DpCloudServerContext', 'HDFSContext', 'LazyLocalContext',
'LocalContext', 'SSHContext'}

read_file(*fname*)

```

subclasses_dict = {'DpCloudServer': <class
'dpdispatcher.dp_cloud_server_context.DpCloudServerContext'>,
'DpCloudServerContext': <class
'dpdispatcher.dp_cloud_server_context.DpCloudServerContext'>, 'HDFS': <class
'dpdispatcher.hdfs_context.HDFSContext'>, 'HDFSContext': <class
'dpdispatcher.hdfs_context.HDFSContext'>, 'LazyLocal': <class
'dpdispatcher.lazy_local_context.LazyLocalContext'>, 'LazyLocalContext': <class
'dpdispatcher.lazy_local_context.LazyLocalContext'>, 'Local': <class
'dpdispatcher.local_context.LocalContext'>, 'LocalContext': <class
'dpdispatcher.local_context.LocalContext'>, 'SSH': <class
'dpdispatcher.ssh_context.SSHContext'>, 'SSHContext': <class
'dpdispatcher.ssh_context.SSHContext'>, 'dpcloudserver': <class
'dpdispatcher.dp_cloud_server_context.DpCloudServerContext'>,
'dpcloudservercontext': <class
'dpdispatcher.dp_cloud_server_context.DpCloudServerContext'>, 'hdfs': <class
'dpdispatcher.hdfs_context.HDFSContext'>, 'hdfscontext': <class
'dpdispatcher.hdfs_context.HDFSContext'>, 'lazylocal': <class
'dpdispatcher.lazy_local_context.LazyLocalContext'>, 'lazylocalcontext': <class
'dpdispatcher.lazy_local_context.LazyLocalContext'>, 'local': <class
'dpdispatcher.local_context.LocalContext'>, 'localcontext': <class
'dpdispatcher.local_context.LocalContext'>, 'ssh': <class
'dpdispatcher.ssh_context.SSHContext'>, 'sshcontext': <class
'dpdispatcher.ssh_context.SSHContext'>}

upload(submission)

write_file(fname, write_str)

```

6.1.5 dpdispatcher.distributed_shell module

```

class dpdispatcher.distributed_shell.DistributedShell(*args, **kwargs)
Bases: dpdispatcher.machine.Machine

```

Methods

<code>do_submit(job)</code>	submit th job to yarn using distributed shell
<code>resources_arginfo()</code>	Generate the resources arginfo.
<code>resources_subfields()</code>	Generate the resources subfields.

arginfo	
bind_context	
check_finish_tag	
check_if_recover	
check_status	
default_resources	
gen_command_env_cuda_devices	
gen_script	
gen_script_command	
gen_script_custom_flags_lines	
gen_script_end	
gen_script_env	
gen_script_header	
gen_script_wait	
load_from_dict	
load_from_json	
sub_script_cmd	
sub_script_head	

check_finish_tag(*job*)

check_status(*job*)

do_submit(*job*)

submit th job to yarn using distributed shell

Parameters

job [Job class instance] job to be submitted

Returns

job_id: string submit process id

gen_script_end(*job*)

gen_script_env(*job*)

gen_script_header(*job*)

6.1.6 dpdispatcher.dp_cloud_server module

```
class dpdispatcher.dp_cloud_server.DpCloudServer(*args, **kwargs)
Bases: dpdispatcher.machine.Machine
```

Methods

<code>do_submit(job)</code>	submit a single job, assuming that no job is running there.
<code>resources_arginfo()</code>	Generate the resources arginfo.
<code>resources_subfields()</code>	Generate the resources subfields.

<code>arginfo</code>	
<code>bind_context</code>	
<code>check_finish_tag</code>	
<code>check_if_recover</code>	
<code>check_status</code>	
<code>default_resources</code>	
<code>gen_command_env_cuda_devices</code>	
<code>gen_local_script</code>	
<code>gen_script</code>	
<code>gen_script_command</code>	
<code>gen_script_custom_flags_lines</code>	
<code>gen_script_end</code>	
<code>gen_script_env</code>	
<code>gen_script_header</code>	
<code>gen_script_wait</code>	
<code>load_from_dict</code>	
<code>load_from_json</code>	
<code>map_dp_job_state</code>	
<code>sub_script_cmd</code>	
<code>sub_script_head</code>	

`check_finish_tag(job)`

`check_if_recover(submission)`

`check_status(job)`

`do_submit(job)`

submit a single job, assuming that no job is running there.

`gen_local_script(job)`

`gen_script(job)`

`gen_script_header(job)`

`static map_dp_job_state(status)`

6.1.7 dpdispatcher.dp_cloud_server_context module

```
class dpdispatcher.dp_cloud_server_context.DpCloudServerContext(*args, **kwargs)
    Bases: dpdispatcher.base_context.BaseContext
```

Methods

<code>machine_arginfo()</code>	Generate the machine arginfo.
<code>machine_subfields()</code>	Generate the machine subfields.

<code>bind_submission</code>	
<code>check_file_exists</code>	
<code>check_finish</code>	
<code>check_home_file_exists</code>	
<code>clean</code>	
<code>download</code>	
<code>kill</code>	
<code>load_from_dict</code>	
<code>read_file</code>	
<code>read_home_file</code>	
<code>upload</code>	
<code>write_file</code>	
<code>write_home_file</code>	
<code>write_local_file</code>	

`bind_submission(submission)`

`check_file_exists(fname)`

`check_home_file_exists(fname)`

`clean()`

`download(submission)`

`kill(cmd_pipes)`

`classmethod load_from_dict(context_dict)`

`classmethod machine_subfields() → List[dargs.dargs.Argument]`
Generate the machine subfields.

Returns

`list[Argument]` machine subfields

`read_file(fname)`

```
read_home_file(fname)
upload(submission)
write_file(fname, write_str)
write_home_file(fname, write_str)
write_local_file(fname, write_str)
```

6.1.8 dpdispatcher.dpdisp module

`dpdispatcher.dpdisp.main()`

6.1.9 dpdispatcher.hdfs_cli module

`class dpdispatcher.hdfs_cli.HDFS`
Bases: `object`

Fundamental class for HDFS basic manipulation

Methods

<code>copy_from_local</code> (<i>local_path</i> , <i>to_uri</i>)	Returns: True on success Raises: on unexpected error
<code>exists</code> (<i>uri</i>)	Check existence of hdfs uri Returns: True on exists Raises: RuntimeError
<code>mkdir</code> (<i>uri</i>)	Make new hdfs directory Returns: True on success Raises: RuntimeError
<code>remove</code> (<i>uri</i>)	Check existence of hdfs uri Returns: True on exists Raises: RuntimeError

<code>copy_to_local</code>		
<code>move</code>		
<code>read_hdfs_file</code>		

`static copy_from_local`(*local_path*, *to_uri*)
Returns: True on success
Raises: on unexpected error

`static copy_to_local`(*from_uri*, *local_path*)

`static exists`(*uri*)
Check existence of hdfs uri
Returns: True on exists
Raises: RuntimeError

`static mkdir`(*uri*)
Make new hdfs directory
Returns: True on success
Raises: RuntimeError

```
static move(from_uri, to_uri)

static read_hdfs_file(uri)

static remove(uri)
    Check existence of hdfs uri Returns: True on exists Raises: RuntimeError
```

6.1.10 dpdispatcher.hdfs_context module

```
class dpdispatcher.hdfs_context.HDFSContext(*args, **kwargs)
    Bases: dpdispatcher.base_context.BaseContext
```

Methods

<code>download(submission[, check_exists, ...])</code>	download backward files from HDFS root dir
<code>machine_arginfo()</code>	Generate the machine arginfo.
<code>machine_subfields()</code>	Generate the machine subfields.
<code>upload(submission[, dereference])</code>	upload forward files and forward command files to HDFS root dir

<code>bind_submission</code>	
<code>check_file_exists</code>	
<code>check_finish</code>	
<code>clean</code>	
<code>get_job_root</code>	
<code>kill</code>	
<code>load_from_dict</code>	
<code>read_file</code>	
<code>write_file</code>	

`bind_submission(submission)`

`check_file_exists(fname)`

`clean()`

`download(submission, check_exists=False, mark_failure=True, back_error=False)`
download backward files from HDFS root dir

Parameters

`submission` [Submission class instance] represents a collection of tasks, such as backward file names

Returns

`none`

`get_job_root()`

```

classmethod load_from_dict(context_dict)

read_file(fname)

upload(submission, dereference=True)
    upload forward files and forward command files to HDFS root dir

```

Parameters

submission [Submission class instance] represents a collection of tasks, such as forward file names

Returns

none

write_file(fname, write_str)

6.1.11 dpdispatcher.lazy_local_context module

```

class dpdispatcher.lazy_local_context.LazyLocalContext(*args, **kwargs)
Bases: dpdispatcher.base_context.BaseContext

```

Methods

machine_arginfo()	Generate the machine arginfo.
machine_subfields()	Generate the machine subfields.

bind_submission	
block_call	
block_checkcall	
call	
check_file_exists	
check_finish	
clean	
download	
get_job_root	
get_return	
kill	
load_from_dict	
read_file	
upload	
write_file	

bind_submission(submission)

block_call(cmd)

```
block_checkcall(cmd)

call(cmd)

check_file_exists(fname)

check_finish(proc)

clean()

download(jobs, check_exists=False, mark_failure=True, back_error=False)

get_job_root()

get_return(proc)

kill(proc)

classmethod load_from_dict(context_dict)

read_file(fname)

upload(jobs, dereference=True)

write_file(fname, write_str)

class dpdispatcher.lazy_local_context.SPRetObj(ret)
    Bases: object
```

Methods

read	
readlines	

read()

readlines()

6.1.12 dpdispatcher.local_context module

```
class dpdispatcher.local_context.LocalContext(*args, **kwargs)
    Bases: dpdispatcher.base_context.BaseContext
```

Methods

<code>machine_arginfo()</code>	Generate the machine arginfo.
<code>machine_subfields()</code>	Generate the machine subfields.

<code>bind_submission</code>	
<code>block_call</code>	
<code>block_checkcall</code>	
<code>call</code>	
<code>check_file_exists</code>	
<code>check_finish</code>	
<code>clean</code>	
<code>download</code>	
<code>download_</code>	
<code>get_job_root</code>	
<code>get_return</code>	
<code>kill</code>	
<code>load_from_dict</code>	
<code>read_file</code>	
<code>upload</code>	
<code>upload_</code>	
<code>write_file</code>	

`bind_submission(submission)`

`block_call(cmd)`

`block_checkcall(cmd)`

`call(cmd)`

`check_file_exists(fname)`

`check_finish(proc)`

`clean()`

`download(submission, check_exists=False, mark_failure=True, back_error=False)`

`download_(job_dirs, remote_down_files, check_exists=False, mark_failure=True, back_error=False)`

DPDispatcher

```
get_job_root()  
  
get_return(proc)  
  
kill(proc)  
  
classmethod load_from_dict(context_dict)  
  
read_file(fname)  
  
upload(submission)  
  
upload_(job_dirs, local_up_files, dereference=True)  
  
write_file(fname, write_str)  
  
class dpdispatcher.local_context.SPRetObj(ret)  
Bases: object
```

Methods

read	
readlines	

read()

readlines()

6.1.13 dpdispatcher.lsf module

```
class dpdispatcher.lsf.LSF(*args, **kwargs)  
Bases: dpdispatcher.machine.Machine  
LSF batch
```

Methods

default_resources(resources)

do_submit(job)	submit a single job, assuming that no job is running there.
resources_arginfo()	Generate the resources arginfo.
resources_subfields()	Generate the resources subfields.

arginfo	
bind_context	
check_finish_tag	
check_if_recover	
check_status	
gen_command_env_cuda_devices	
gen_script	
gen_script_command	
gen_script_custom_flags_lines	
gen_script_end	
gen_script_env	
gen_script_header	
gen_script_wait	
load_from_dict	
load_from_json	
sub_script_cmd	
sub_script_head	

check_finish_tag(*job*)

check_status(*job*)

default_resources(*resources*)

do_submit(*job*)

submit a single job, assuming that no job is running there.

gen_script(*job*)

gen_script_header(*job*)

classmethod resources_subfields() → List[dargs.dargs.Argument]

Generate the resources subfields.

Returns

list[Argument] resources subfields

sub_script_cmd(*res*)

sub_script_head(*res*)

6.1.14 dppdispatcher.machine module

```
class dppdispatcher.machine.Machine(*args, **kwargs)
    Bases: object
```

A machine is used to handle the connection with remote machines.

Parameters

context [SubClass derived fromBaseContext] The context is used to mainatin the connection with remote machine.

Methods

<code>do_submit(job)</code>	submit a single job, assuming that no job is running there.
<code>resources_arginfo()</code>	Generate the resources arginfo.
<code>resources_subfields()</code>	Generate the resources subfields.

<code>arginfo</code>	
<code>bind_context</code>	
<code>check_finish_tag</code>	
<code>check_if_recover</code>	
<code>check_status</code>	
<code>default_resources</code>	
<code>gen_command_env_cuda_devices</code>	
<code>gen_script</code>	
<code>gen_script_command</code>	
<code>gen_script_custom_flags_lines</code>	
<code>gen_script_end</code>	
<code>gen_script_env</code>	
<code>gen_script_header</code>	
<code>gen_script_wait</code>	
<code>load_from_dict</code>	
<code>load_from_json</code>	
<code>sub_script_cmd</code>	
<code>sub_script_head</code>	

`classmethod arginfo()`

`bind_context(context)`

`check_finish_tag(**kwargs)`

`check_if_recover(submission)`

`check_status(job)`

`default_resources(res)`

```
do_submit(job)
    submit a single job, assuming that no job is running there.

gen_command_env_cuda_devices(resources)

gen_script(job)

gen_script_command(job)

gen_script_custom_flags_lines(job)

gen_script_end(job)

gen_script_env(job)

gen_script_header(job)

gen_script_wait(resources)

classmethod load_from_dict(machine_dict)

classmethod load_from_json(json_path)

options = {'DistributedShell', 'DpCloudServer', 'LSF', 'PBS', 'Shell', 'Slurm',
'Torque'}

classmethod resources_arginfo() → dargs.dargs.Argument
    Generate the resources arginfo.

    Returns
        Argument resources arginfo

    classmethod resources_subfields() → List[dargs.dargs.Argument]
        Generate the resources subfields.

        Returns
            list[Argument] resources subfields

    sub_script_cmd(res)

    sub_script_head(res)
```

```
subclasses_dict = {'DistributedShell': <class
'dpdispatcher.distributed_shell.DistributedShell'>, 'DpCloudServer': <class
'dpdispatcher.dp_cloud_server.DpCloudServer'>, 'LSF': <class
'dpdispatcher.lsf.LSF'>, 'PBS': <class 'dpdispatcher.pbs.PBS'>, 'Shell': <class
'dpdispatcher.shell.Shell'>, 'Slurm': <class 'dpdispatcher.slurm.Slurm'>, 'Torque': <class
'dpdispatcher.pbs.Torque'>, 'distributedshell': <class
'dpdispatcher.distributed_shell.DistributedShell'>, 'dpcloudserver': <class
'dpdispatcher.dp_cloud_server.DpCloudServer'>, 'lsf': <class
'dpdispatcher.lsf.LSF'>, 'pbs': <class 'dpdispatcher.pbs.PBS'>, 'shell': <class
'dpdispatcher.shell.Shell'>, 'slurm': <class 'dpdispatcher.slurm.Slurm'>, 'torque': <class
'dpdispatcher.pbs.Torque'>}
```

6.1.15 dpdispatcher.pbs module

```
class dpdispatcher.pbs.PBS(*args, **kwargs)
Bases: dpdispatcher.machine.Machine
```

Methods

<code>do_submit(job)</code>	submit a single job, assuming that no job is running there.
<code>resources_arginfo()</code>	Generate the resources arginfo.
<code>resources_subfields()</code>	Generate the resources subfields.

<code>arginfo</code>
<code>bind_context</code>
<code>check_finish_tag</code>
<code>check_if_recover</code>
<code>check_status</code>
<code>default_resources</code>
<code>gen_command_env_cuda_devices</code>
<code>gen_script</code>
<code>gen_script_command</code>
<code>gen_script_custom_flags_lines</code>
<code>gen_script_end</code>
<code>gen_script_env</code>
<code>gen_script_header</code>
<code>gen_script_wait</code>
<code>load_from_dict</code>
<code>load_from_json</code>
<code>sub_script_cmd</code>
<code>sub_script_head</code>

`check_finish_tag(job)`

`check_status(job)`

`default_resources(resources)`

```

do_submit(job)
    submit a single job, assuming that no job is running there.

gen_script(job)

gen_script_header(job)

class dpdispatcher.pbs.Torque(*args, **kwargs)
    Bases: dpdispatcher.pbs.PBS

```

Methods

do_submit(job)	submit a single job, assuming that no job is running there.
resources_arginfo()	Generate the resources arginfo.
resources_subfields()	Generate the resources subfields.

arginfo	
bind_context	
check_finish_tag	
check_if_recover	
check_status	
default_resources	
gen_command_env_cuda_devices	
gen_script	
gen_script_command	
gen_script_custom_flags_lines	
gen_script_end	
gen_script_env	
gen_script_header	
gen_script_wait	
load_from_dict	
load_from_json	
sub_script_cmd	
sub_script_head	

check_status(job)

6.1.16 dpdispatcher.shell module

```
class dpdispatcher.shell.Shell(*args, **kwargs)
    Bases: dpdispatcher.machine.Machine
```

Methods

<code>do_submit(job)</code>	submit a single job, assuming that no job is running there.
<code>resources_arginfo()</code>	Generate the resources arginfo.
<code>resources_subfields()</code>	Generate the resources subfields.

<code>arginfo</code>	
<code>bind_context</code>	
<code>check_finish_tag</code>	
<code>check_if_recover</code>	
<code>check_status</code>	
<code>default_resources</code>	
<code>gen_command_env_cuda_devices</code>	
<code>gen_script</code>	
<code>gen_script_command</code>	
<code>gen_script_custom_flags_lines</code>	
<code>gen_script_end</code>	
<code>gen_script_env</code>	
<code>gen_script_header</code>	
<code>gen_script_wait</code>	
<code>load_from_dict</code>	
<code>load_from_json</code>	
<code>sub_script_cmd</code>	
<code>sub_script_head</code>	

`check_finish_tag(job)`

`check_status(job)`

`default_resources(resources)`

`do_submit(job)`

submit a single job, assuming that no job is running there.

`gen_script(job)`

`gen_script_header(job)`

6.1.17 dpdispatcher.slurm module

```
class dpdispatcher.slurm.Slurm(*args, **kwargs)
    Bases: dpdispatcher.machine.Machine
```

Methods

<code>do_submit(job[, retry, max_retry])</code>	submit a single job, assuming that no job is running there.
<code>resources_arginfo()</code>	Generate the resources arginfo.
<code>resources_subfields()</code>	Generate the resources subfields.

<code>arginfo</code>	
<code>bind_context</code>	
<code>check_finish_tag</code>	
<code>check_if_recover</code>	
<code>check_status</code>	
<code>default_resources</code>	
<code>gen_command_env_cuda_devices</code>	
<code>gen_script</code>	
<code>gen_script_command</code>	
<code>gen_script_custom_flags_lines</code>	
<code>gen_script_end</code>	
<code>gen_script_env</code>	
<code>gen_script_header</code>	
<code>gen_script_wait</code>	
<code>load_from_dict</code>	
<code>load_from_json</code>	
<code>sub_script_cmd</code>	
<code>sub_script_head</code>	

`check_finish_tag(job)`

`check_status(job, retry=0, max_retry=3)`

`default_resources(resources)`

`do_submit(job, retry=0, max_retry=3)`

submit a single job, assuming that no job is running there.

`gen_script(job)`

`gen_script_header(job)`

`classmethod resources_subfields() → List[dargs.dargs.Argument]`

Generate the resources subfields.

Returns

list[Argument] resources subfields

6.1.18 `dpdispatcher.ssh_context` module

```
class dpdispatcher.ssh_context.SSHContext(*args, **kwargs)
Bases: dpdispatcher.base_context.BaseContext
```

Attributes

`sftp`

`ssh`

Methods

<code>block_checkcall(cmd[, asynchronously, ...])</code>	Run command with arguments.
<code>machine_arginfo()</code>	Generate the machine arginfo.
<code>machine_subfields()</code>	Generate the machine subfields.

<code>bind_submission</code>	
<code>block_call</code>	
<code>call</code>	
<code>check_file_exists</code>	
<code>check_finish</code>	
<code>clean</code>	
<code>close</code>	
<code>download</code>	
<code>get_job_root</code>	
<code>get_return</code>	
<code>kill</code>	
<code>load_from_dict</code>	
<code>read_file</code>	
<code>upload</code>	
<code>write_file</code>	

`bind_submission(submission)`

`block_call(cmd)`

`block_checkcall(cmd, asynchronously=False, stderr_whitelist=None)`

Run command with arguments. Wait for command to complete. If the return code was zero then return, otherwise raise RuntimeError.

Parameters

`cmd: str` The command to run.

`asynchronously: bool, optional, default=False` Run command asynchronously. If True, `nohup` will be used to run the command.

`call(cmd)`

```
check_file_exists(fname)

check_finish(cmd_pipes)

clean()

close()

download(submission, check_exists=False, mark_failure=True, back_error=False)

get_job_root()

get_return(cmd_pipes)

kill(cmd_pipes)

classmethod load_from_dict(context_dict)

classmethod machine_subfields() → List[dargs.dargs.Argument]
    Generate the machine subfields.

    Returns
        list[Argument] machine subfields

read_file(fname)

property sftp

property ssh

upload(submission, dereference=True)

write_file(fname, write_str)

class dpdispatcher.ssh_context.SSHSession(hostname, username, password=None, port=22,
                                         key_filename=None, passphrase=None, timeout=10,
                                         totp_secret=None)
Bases: object

Attributes
    sftp Returns sftp.
```

Methods

<code>exec_command(cmd[, retry])</code>	Calling self.ssh.exec_command but has an exception check.
---	---

arginfo	
close	
ensure_alive	
get_ssh_client	

```
static arginfo()

close()

ensure_alive(max_check=10, sleep_time=10)

exec_command(cmd, retry=0)
    Calling self.ssh.exec_command but has an exception check.

get_ssh_client()

property sftp
    Returns sftp. Open a new one if not existing.
```

6.1.19 dpdispatcher.submission module

```
class dpdispatcher.submission.Job(job_task_list, *, resources, machine=None)
Bases: object
```

Job is generated by Submission automatically. A job ususally has many tasks and it may request computing resources from job scheduler systems. Each Job can generate a script file to be submitted to the job scheduler system or executed locally.

Parameters

- job_task_list** [list of Task] the tasks belonging to the job
- resources** [Resources] the machine resources. Passed from Submission when it constructs jobs.
- machine** [machine] machine object to execute the job. Passed from Submission when it constructs jobs.

Methods

<code>deserialize(job_dict[, machine])</code>	convert the job_dict to a Submission class object
<code>get_job_state()</code>	get the jobs.
<code>serialize([if_static])</code>	convert the Task class instance to a dictionary.

<code>get_hash</code>	
<code>handle_unexpected_job_state</code>	
<code>job_to_json</code>	
<code>register_job_id</code>	
<code>submit_job</code>	

`classmethod deserialize(job_dict, machine=None)`

convert the job_dict to a Submission class object

Parameters

`submission_dict` [dict] path-like, the base directory of the local tasks

Returns

`submission` [Job] the Job class instance converted from the job_dict

`get_hash()`

`get_job_state()`

get the jobs. Usually, this method will query the database of slurm or pbs job scheduler system and get the results.

Notes

this method will not submit or resubmit the jobs if the job is unsubmitted.

`handle_unexpected_job_state()`

`job_to_json()`

`register_job_id(job_id)`

`serialize(if_static=False)`

convert the Task class instance to a dictionary.

Parameters

`if_static` [bool] whether dump the job runtime infomation (job_id, job_state, fail_count, job_uuid etc.) to the dictionary.

Returns

`task_dict` [dict] the dictionary converted from the Task class instance

`submit_job()`

```
class dpdispatcher.submission.Resources(number_node, cpu_per_node, gpu_per_node, queue_name,
                                         group_size, *, custom_flags=[],  
                                         strategy={'if_cuda_multi_devices': False}, para_deg=1,  
                                         module_unload_list=[], module_list=[], source_list=[],  
                                         envs={}, **kwargs)
```

Bases: `object`

Resources is used to describe the machine resources we need to do calculations.

Parameters

number_node [int] The number of node need for each *job*.

cpu_per_node [int] cpu numbers of each node.

gpu_per_node [int] gpu numbers of each node.

queue_name [str] The queue name of batch job scheduler system.

group_size [int] The number of *tasks* in a *job*.

custom_flags [list of Str] The extra lines pass to job submitting script header

strategy [dict] strategies we use to generation job submitting scripts. `if_cuda_multi_devices` : bool
If there are multiple nvidia GPUS on the node, and we want to assign the tasks to different GPUS. If true, dpdispatcher will manually export environment variable CUDA_VISIBLE_DEVICES to different task. Usually, this option will be used with Task.task_need_resources variable simultaneously.

para_deg [int] Decide how many tasks will be run in parallel. Usually run with `strategy['if_cuda_multi_devices']`

source_list [list of Path] The env file to be sourced before the command execution.

Methods

<code>arginfo</code>	
<code>deserialize</code>	
<code>load_from_dict</code>	
<code>load_from_json</code>	
<code>serialize</code>	

```
static arginfo()  
  
classmethod deserialize(resources_dict)  
  
classmethod load_from_dict(resources_dict)  
  
classmethod load_from_json(json_file)  
  
serialize()
```

```
class dpdispatcher.submission.Submission(work_base, machine=None, resources=None,
                                         forward_common_files=[], backward_common_files=[], *,
                                         task_list=[])
Bases: object
```

A submission represents a collection of tasks. These tasks usually locate at a common directory. And these Tasks may share common files to be uploaded and downloaded.

Parameters

- work_base** [Path] the base directory of the local tasks. It is usually the dir name of project .
- machine** [Machine] machine class object (for example, PBS, Slurm, Shell) to execute the jobs.
The machine can still be bound after the instantiation with the bind_submission method.
- resources** [Resources] the machine resources (cpu or gpu) used to generate the slurm/pbs script
- forward_common_files** [list] the common files to be uploaded to other computers before the jobs begin
- backward_common_files** [list] the common files to be downloaded from other computers after the jobs finish
- task_list** [list of Task] a list of tasks to be run.

Methods

<code>bind_machine(machine)</code>	bind this submission to a machine.
<code>check_all_finished()</code>	check whether all the jobs in the submission.
<code>deserialize(submission_dict[, machine])</code>	convert the submission_dict to a Submission class object
<code>generate_jobs()</code>	After tasks register to the self.belonging_tasks, This method generate the jobs and add these jobs to self.belonging_jobs.
<code>handle_unexpected_submission_state()</code>	handle unexpected job state of the submission.
<code>run_submission(*[, exit_on_submit, clean])</code>	main method to execute the submission.
<code>serialize([if_static, if_none_local_root])</code>	convert the Submission class instance to a dictionary.
<code>update_submission_state()</code>	check whether all the jobs in the submission.

<code>clean_jobs</code>	
<code>download_jobs</code>	
<code>get_hash</code>	
<code>register_task</code>	
<code>register_task_list</code>	
<code>submission_from_json</code>	
<code>submission_to_json</code>	
<code>try_recover_from_json</code>	
<code>upload_jobs</code>	

bind_machine(machine)

bind this submission to a machine. update the machine's context remote_root and local_root.

Parameters

- machine** [Machine] the machine to bind with

check_all_finished()

check whether all the jobs in the submission.

Notes

This method will not handle unexpected job state in the submission.

clean_jobs()**classmethod deserialize(submission_dict, machine=None)**

convert the submission_dict to a Submission class object

Parameters

submission_dict [dict] path-like, the base directory of the local tasks

Returns

submission [Submission] the Submission class instance converted from the submission_dict

download_jobs()**generate_jobs()**

After tasks register to the self.belonging_tasks, This method generate the jobs and add these jobs to self.belonging_jobs. The jobs are generated by the tasks randomly, and there are self.resources.group_size tasks in a task. Why we randomly shuffle the tasks is under the consideration of load balance. The random seed is a constant (to be concrete, 42). And this insures that the jobs are equal when we re-run the program.

get_hash()**handle_unexpected_submission_state()**

handle unexpected job state of the submission. If the job state is unsubmitted, submit the job. If the job state is terminated (killed unexpectedly), resubmit the job. If the job state is unknown, raise an error.

register_task(task)**register_task_list(task_list)****run_submission(*, exit_on_submit=False, clean=True)**

main method to execute the submission. First, check whether old Submission exists on the remote machine, and try to recover from it. Second, upload the local files to the remote machine where the tasks to be executed. Third, run the submission defined previously. Forth, wait until the tasks in the submission finished and download the result file to local directory. if exit_on_submit is True, submission will exit.

serialize(if_static=False, if_none_local_root=False)

convert the Submission class instance to a dictionary.

Parameters

if_static [bool] whether dump the job runtime infomation (like job_id, job_state, fail_count) to the dictionary.

Returns

submission_dict [dict] the dictionary converted from the Submission class instance

classmethod submission_from_json(json_file_name='submission.json')

submission_to_json()

try_recover_from_json()

update_submission_state()
check whether all the jobs in the submission.

Notes

this method will not handle unexpected (like resubmit terminated) job state in the submission.

upload_jobs()

```
class dpdispatcher.submission.Task(command, task_work_path, forward_files=[], backward_files=[],
                                    outlog='log', errlog='err')
```

Bases: `object`

A task is a sequential command to be executed, as well as the files it depends on to transmit forward and backward.

Parameters

command [Str] the command to be executed.

task_work_path [Path] the directory of each file where the files are dependent on.

forward_files [list of Path] the files to be transmitted to remote machine before the command execute.

backward_files [list of Path] the files to be transmitted from remote machine after the command finished.

outlog [Str] the filename to which command redirect stdout

errlog [Str] the filename to which command redirect stderr

Methods

<code>deserialize(task_dict)</code>	convert the task_dict to a Task class object
-------------------------------------	--

<code>arginfo</code>	
<code>get_hash</code>	
<code>load_from_json</code>	
<code>serialize</code>	

static arginfo()

classmethod deserialize(task_dict)
convert the task_dict to a Task class object

Parameters

task_dict [dict] the dictionary which contains the task information

Returns

```
task [Task] the Task class instance converted from the task_dict  
get_hash()  
  
classmethod load_from_json(json_file)  
  
serialize()
```

6.1.20 dpdispatcher.utils module

`dpdispatcher.utils.generate_totp(secret: str, period: int = 30, token_length: int = 6) → int`
Generate time-based one time password (TOTP) from the secret.

Some HPCs use TOTP for two-factor authentication for safety.

Parameters

secret: str The encoded secret provided by the HPC. It's usually extracted from a 2D code and base32 encoded.
period: int, default=30 Time period where the code is valid in seconds.
token_length: int, default=6 The token length.

Returns

token: int The generated token.

References

<https://github.com/lepture/otpauth/blob/49914d83d36dbcd33c9e26f65002b21ce09a6303/otpauth.py#L143-L160>

`dpdispatcher.utils.get_sha256(filename)`
Get sha256 of a file.

Parameters

filename: str The filename.

Returns

sha256: str The sha256.

`dpdispatcher.utils.run_cmd_with_all_output(cmd)`

CHAPTER
SEVEN

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

d

dpdispatcher, 19
dpdispatcher.base_context, 21
dpdispatcher.distributed_shell, 23
dpdispatcher.dp_cloud_server, 24
dpdispatcher.dp_cloud_server_context, 26
dpdispatcher.dpcloudserver, 19
dpdispatcher.dpcloudserver.api, 19
dpdispatcher.dpcloudserver.config, 20
dpdispatcher.dpcloudserver.retcode, 20
dpdispatcher.dpcloudserver.zip_file, 21
dpdispatcher.dpdisp, 27
dpdispatcher.hdfs_cli, 27
dpdispatcher.hdfs_context, 28
dpdispatcher.JobStatus, 21
dpdispatcher.lazy_local_context, 29
dpdispatcher.local_context, 31
dpdispatcher.lsf, 32
dpdispatcher.machine, 34
dpdispatcher.pbs, 36
dpdispatcher.shell, 38
dpdispatcher.slurm, 39
dpdispatcher.ssh_context, 40
dpdispatcher.submission, 42
dpdispatcher.utils, 48

INDEX

A

API (class in `dpdispatcher.dpcloudserver.api`), 19
`arginfo()` (`dpdispatcher.machine.Machine` class method), 34
`arginfo()` (`dpdispatcher.ssh_context.SSHSession` static method), 42
`arginfo()` (`dpdispatcher.submission.Resources` static method), 44
`arginfo()` (`dpdispatcher.submission.Task` static method), 47

B

`BaseContext` (class in `dpdispatcher.base_context`), 21
`bind_context()` (`dpdispatcher.machine.Machine` method), 34
`bind_machine()` (`dpdispatcher.submission.Submission` method), 45
`bind_submission()` (`dpdispatcher.base_context.BaseContext` method), 22
`bind_submission()` (`dpdispatcher.dp_cloud_server_context.DpCloudServerContext` method), 26
`bind_submission()` (`dpdispatcher.hdfs_context.HDFSContext` method), 28
`bind_submission()` (`dpdispatcher.lazy_local_context.LazyLocalContext` method), 29
`bind_submission()` (`dpdispatcher.local_context.LocalContext` method), 31
`bind_submission()` (`dpdispatcher.ssh_context.SSHContext` method), 40
`block_call()` (`dpdispatcher.lazy_local_context.LazyLocalContext` method), 29
`block_call()` (`dpdispatcher.local_context.LocalContext` method), 31
`block_call()` (`dpdispatcher.ssh_context.SSHContext` method), 40
`block_checkcall()` (`dpdis-`

`patcher.lazy_local_context.LazyLocalContext` method), 29

`block_checkcall()` (`dpdispatcher.local_context.LocalContext` method), 31
`block_checkcall()` (`dpdispatcher.ssh_context.SSHContext` method), 40

C

`call()` (`dpdispatcher.lazy_local_context.LazyLocalContext` method), 30
`call()` (`dpdispatcher.local_context.LocalContext` method), 31
`call()` (`dpdispatcher.ssh_context.SSHContext` method), 40
`check_all_finished()` (`dpdispatcher.submission.Submission` method), 45
`check_file_exists()` (`dpdispatcher.dp_cloud_server_context.DpCloudServerContext` method), 26
`check_file_exists()` (`dpdispatcher.hdfs_context.HDFSContext` method), 28
`check_file_exists()` (`dpdispatcher.lazy_local_context.LazyLocalContext` method), 30
`check_file_exists()` (`dpdispatcher.local_context.LocalContext` method), 31
`check_file_exists()` (`dpdispatcher.ssh_context.SSHContext` method), 40
`check_finish()` (`dpdispatcher.base_context.BaseContext` method), 22
`check_finish()` (`dpdispatcher.lazy_local_context.LazyLocalContext` method), 30
`check_finish()` (`dpdispatcher.local_context.LocalContext` method),

31
check_finish() (*dpdispatcher.ssh_context.SSHContext method*), 41
check_finish_tag() (*dpdispatcher.distributed_shell.DistributedShell method*), 24
check_finish_tag() (*dpdispatcher.dp_cloud_server.DpCloudServer method*), 25
check_finish_tag() (*dpdispatcher.lsf.LSF method*), 33
check_finish_tag() (*dpdispatcher.machine.Machine method*), 34
check_finish_tag() (*dpdispatcher.pbs.PBS method*), 36
check_finish_tag() (*dpdispatcher.shell.Shell method*), 38
check_finish_tag() (*dpdispatcher.slurm.Slurm method*), 39
check_home_file_exists() (*dpdispatcher.dp_cloud_server_context.DpCloudServerContext method*), 26
check_if_recover() (*dpdispatcher.dp_cloud_server.DpCloudServer method*), 25
check_if_recover() (*dpdispatcher.machine.Machine method*), 34
check_status() (*dpdispatcher.distributed_shell.DistributedShell method*), 24
check_status() (*dpdispatcher.dp_cloud_server.DpCloudServer method*), 25
check_status() (*dpdispatcher.lsf.LSF method*), 33
check_status() (*dpdispatcher.machine.Machine method*), 34
check_status() (*dpdispatcher.pbs.PBS method*), 36
check_status() (*dpdispatcher.pbs.Torque method*), 37
check_status() (*dpdispatcher.shell.Shell method*), 38
check_status() (*dpdispatcher.slurm.Slurm method*), 39
clean() (*dpdispatcher.base_context.BaseContext method*), 22
clean() (*dpdispatcher.dp_cloud_server_context.DpCloudServerContext method*), 26
clean() (*dpdispatcher.hdfs_context.HDFSContext method*), 28
clean() (*dpdispatcher.lazy_local_context.LazyLocalContext method*), 30
clean() (*dpdispatcher.local_context.LocalContext method*), 31
clean() (*dpdispatcher.ssh_context.SSHContext method*), 41
clean_jobs() (*dpdispatcher.submission.Submission method*), 46
close() (*dpdispatcher.ssh_context.SSHContext method*), 41
close() (*dpdispatcher.ssh_context.SSHSession method*), 42
completing (*dpdispatcher.JobStatus.JobStatus attribute*), 21
copy_from_local() (*dpdispatcher.hdfs_cli.HDFS static method*), 27
copy_to_local() (*dpdispatcher.hdfs_cli.HDFS static method*), 27

D

DATAERR (*dpdispatcher.dpcloudserver.retcodes.RETCODE attribute*), 20
DBERR (*dpdispatcher.dpcloudserver.retcodes.RETCODE attribute*), 20
default_resources() (*dpdispatcher.lsf.LSF method*), 33
default_resources() (*dpdispatcher.machine.Machine method*), 34
default_resources() (*dpdispatcher.pbs.PBS method*), 36
default_resources() (*dpdispatcher.shell.Shell method*), 38
default_resources() (*dpdispatcher.slurm.Slurm method*), 39
deserialize() (*dpdispatcher.submission.Job class method*), 43
deserialize() (*dpdispatcher.submission.Resources class method*), 44
deserialize() (*dpdispatcher.submissionSubmission class method*), 46
deserialize() (*dpdispatcher.submission.Task class method*), 47
DistributedShell (class in *dpdispatcher.distributed_shell*), 23
do_submit() (*dpdispatcher.distributed_shell.DistributedShell method*), 24
do_submit() (*dpdispatcher.dp_cloud_server.DpCloudServer method*), 25
do_submit() (*dpdispatcher.lsf.LSF method*), 33
do_submit() (*dpdispatcher.machine.Machine method*), 34
do_submit() (*dpdispatcher.pbs.PBS method*), 36
do_submit() (*dpdispatcher.shell.Shell method*), 38
do_submit() (*dpdispatcher.slurm.Slurm method*), 39
download() (*dpdispatcher.base_context.BaseContext method*), 22
download() (*dpdispatcher.dp_cloud_server_context.DpCloudServerContext method*), 26
download() (*dpdispatcher.dpcloudserver.api.API method*), 19

```

download() (dpdispatcher.hdfs_context.HDFSContext  dpdispatcher.machine
           method), 28                         module, 34
download() (dpdispatcher.lazy_local_context.LazyLocalContext  dpdispatcher.pbs
           method), 30                         module, 36
download() (dpdispatcher.local_context.LocalContext  dpdispatcher.shell
           method), 31                         module, 38
download() (dpdispatcher.ssh_context.SSHContext  dpdispatcher.slurm
           method), 41                         module, 39
download_() (dpdispatcher.local_context.LocalContext  dpdispatcher.ssh_context
           method), 31                         module, 40
download_from_url()                               (dpdis-  dpdispatcher.submission
                                                patcher.dpcloudserver.api.API  module, 42
                                                19                           dpdispatcher.utils
download_jobs()                               (dpdis-  module, 48
                                                patcher.submission.Submission  method),
                                                46
DpCloudServer (class      in  dpdis-  ensure_alive() (dpdispatcher.ssh_context.SSHSession
           patcher.dp_cloud_server), 24  patcher.dp_cloud_server_context), 26  method), 42
DpCloudServerContext (class      in  dpdis-  exec_command() (dpdispatcher.ssh_context.SSHSession
           patcher.dp_cloud_server_context), 26  method), 42
dpdispatcher  module, 19  exists() (dpdispatcher.hdfs_cli.HDFS static method),
dpdispatcher.base_context  module, 21  27
dpdispatcher.distributed_shell  module, 23
dpdispatcher.dp_cloud_server  module, 24
dpdispatcher.dp_cloud_server_context  module, 26
dpdispatcher.dpcloudserver  module, 19
dpdispatcher.dpcloudserver.api  module, 19
dpdispatcher.dpcloudserver.config  module, 20
dpdispatcher.dpcloudserver.retcode  module, 20
dpdispatcher.dpcloudserver.zip_file  module, 21
dpdispatcher.dpdisp  module, 27
dpdispatcher.hdfs_cli  module, 27
dpdispatcher.hdfs_context  module, 28
dpdispatcher.JobStatus  module, 21
dpdispatcher.lazy_local_context  module, 29
dpdispatcher.local_context  module, 31
dpdispatcher.lsf  module, 32

```

E

```

dpdispatcher.ensure_alive() (dpdispatcher.ssh_context.SSHSession
                           method), 42
dpdispatcher.exec_command() (dpdispatcher.ssh_context.SSHSession
                           method), 42
dpdispatcher.exists() (dpdispatcher.hdfs_cli.HDFS static method),
                      27

```

F

```

dpdispatcher.finished (dpdispatcher.JobStatus.JobStatus attribute),
                      21

```

G

```

dpdispatcher.gen_command_env_cuda_devices() (dpdis-  gen_command_env_cuda_devices() (dpdis-
                                             patcher.machine.Machine method), 35
dpdispatcher.gen_local_script() (dpdis-  gen_local_script() (dpdis-
                                             patcher.dp_cloud_server.DpCloudServer
                                             method), 25
dpdispatcher.gen_script() (dpdispatcher.dp_cloud_server.DpCloudServer
                           method), 25
dpdispatcher.gen_script() (dpdispatcher.lsf.LSF method), 33
dpdispatcher.gen_script() (dpdispatcher.machine.Machine method),
                           35
dpdispatcher.gen_script() (dpdispatcher.pbs.PBS method), 37
dpdispatcher.gen_script() (dpdispatcher.shell.Shell method), 38
dpdispatcher.gen_script() (dpdispatcher.slurm.Slurm method), 39
dpdispatcher.gen_script_command() (dpdis-  gen_script_command() (dpdis-
                                             patcher.machine.Machine method), 35
dpdispatcher.gen_script_custom_flags_lines() (dpdis-  gen_script_custom_flags_lines() (dpdis-
                                             patcher.machine.Machine method), 35
dpdispatcher.gen_script_end() (dpdis-  gen_script_end() (dpdis-
                                             patcher.distributed_shell.DistributedShell
                                             method), 24
dpdispatcher.gen_script_end() (dpdispatcher.machine.Machine
                           method), 35
dpdispatcher.gen_script_env() (dpdis-  gen_script_env() (dpdis-
                                             patcher.distributed_shell.DistributedShell
                                             method), 24

```

gen_script_env() (*dpdispatcher.machine.Machine method*), 35
gen_script_header() (*dpdispatcher.distributed_shell.DistributedShell method*), 24
gen_script_header() (*dpdispatcher.dp_cloud_server.DpCloudServer method*), 25
gen_script_header() (*dpdispatcher.lsf.LSF method*), 33
gen_script_header() (*dpdispatcher.machine.Machine method*), 35
gen_script_header() (*dpdispatcher.pbs.PBS method*), 37
gen_script_header() (*dpdispatcher.shell.Shell method*), 38
gen_script_header() (*dpdispatcher.slurm.Slurm method*), 39
gen_script_wait() (*dpdispatcher.machine.Machine method*), 35
generate_jobs() (*dpdispatcher.submission.Submission method*), 46
generate_totp() (*in module dpdispatcher.utils*), 48
get() (*dpdispatcher.dpcloudserver.api.API method*), 19
get_hash() (*dpdispatcher.submission.Job method*), 43
get_hash() (*dpdispatcher.submissionSubmission method*), 46
get_hash() (*dpdispatcher.submission.Task method*), 48
get_job_root() (*dpdispatcher.hdfs_context.HDFSContext method*), 28
get_job_root() (*dpdispatcher.lazy_local_context.LazyLocalContext method*), 30
get_job_root() (*dpdispatcher.local_context.LocalContext method*), 31
get_job_root() (*dpdispatcher.ssh_context.SSHContext method*), 41
get_job_state() (*dpdispatcher.submission.Job method*), 43
get_jobs() (*dpdispatcher.dpcloudserver.api.API method*), 20
get_return() (*dpdispatcher.lazy_local_context.LazyLocalContext method*), 30
get_return() (*dpdispatcher.local_context.LocalContext method*), 32
get_return() (*dpdispatcher.ssh_context.SSHContext method*), 41
get_sha256() (*in module dpdispatcher.utils*), 48
get_ssh_client() (*dpdispatcher.ssh_context.SSHSession method*), 42
get_tasks() (*dpdispatcher.dpcloudserver.api.API method*), 20
get_tasks_v2() (*dpdispatcher.dpcloudserver.api.API method*), 20
get_tasks_v2_list() (*dpdispatcher.dpcloudserver.api.API method*), 20

H

handle_unexpected_job_state() (*dpdispatcher.submission.Job method*), 43
handle_unexpected_submission_state() (*dpdispatcher.submissionSubmission method*), 46
HDFS (*class in dpdispatcher.hdfs_cli*), 27
HDFSContext (*class in dpdispatcher.hdfs_context*), 28

I

info() (*in module dpdispatcher*), 19
IOERR (*dpdispatcher.dpcloudserver.retcodes.RETCODE attribute*), 20

J

Job (*class in dpdispatcher.submission*), 42
job_create() (*dpdispatcher.dpcloudserver.api.API method*), 20
job_create_v2() (*dpdispatcher.dpcloudserver.api.API method*), 20
job_to_json() (*dpdispatcher.submission.Job method*), 43
JobStatus (*class in dpdispatcher.JobStatus*), 21

K

kill() (*dpdispatcher.base_context.BaseContext method*), 22
kill() (*dpdispatcher.dp_cloud_server_context.DpCloudServerContext method*), 26
kill() (*dpdispatcher.lazy_local_context.LazyLocalContext method*), 30
kill() (*dpdispatcher.local_context.LocalContext method*), 32
kill() (*dpdispatcher.ssh_context.SSHContext method*), 41

L

LazyLocalContext (*class in dpdispatcher.lazy_local_context*), 29
load_from_dict() (*dpdispatcher.base_context.BaseContext class method*), 22
load_from_dict() (*dpdispatcher.dp_cloud_server_context.DpCloudServerContext class method*), 26

`load_from_dict()` (*dpdispatcher.hdfs_context.HDFSContext class method*), 28
`load_from_dict()` (*dpdispatcher.lazy_local_context.LazyLocalContext class method*), 30
`load_from_dict()` (*dpdispatcher.local_context.LocalContext class method*), 32
`load_from_dict()` (*dpdispatcher.machine.Machine class method*), 35
`load_from_dict()` (*dpdispatcher.ssh_context.SSHContext class method*), 41
`load_from_dict()` (*dpdispatcher.submission.Resources class method*), 44
`load_from_json()` (*dpdispatcher.machine.Machine class method*), 35
`load_from_json()` (*dpdispatcher.submission.Resources class method*), 44
`load_from_json()` (*dpdispatcher.submission.Task class method*), 48
`LocalContext` (*class in dpdispatcher.local_context*), 31
`LSF` (*class in dpdispatcher.lsf*), 32

M

`Machine` (*class in dpdispatcher.machine*), 34
`machine_arginfo()` (*dpdispatcher.base_context.BaseContext method*), 22
`machine_subfields()` (*dpdispatcher.base_context.BaseContext method*), 22
`machine_subfields()` (*dpdispatcher.dp_cloud_server_context.DpCloudServerContext class method*), 26
`machine_subfields()` (*dpdispatcher.ssh_context.SSHContext class method*), 41
`main()` (*in module dpdispatcher.dpdisp*), 27
`map_dp_job_state()` (*dpdispatcher.dp_cloud_server.DpCloudServer static method*), 25
`mkdir()` (*dpdispatcher.hdfs_cli.HDFS static method*), 27
`module`

- `dpdispatcher`, 19
- `dpdispatcher.base_context`, 21
- `dpdispatcher.distributed_shell`, 23
- `dpdispatcher.dp_cloud_server`, 24
- `dpdispatcher.dp_cloud_server_context`, 26
- `dpdispatcher.dpcloudserver`, 19
- `dpdispatcher.dpcloudserver.api`, 19

`dpdispatcher.dpcloudserver.config`, 20
`dpdispatcher.dpcloudserver.retcode`, 20
`dpdispatcher.dpcloudserver.zip_file`, 21
`dpdispatcher.dpdisp`, 27
`dpdispatcher.hdfs_cli`, 27
`dpdispatcher.hdfs_context`, 28
`dpdispatcher.JobStatus`, 21
`dpdispatcher.lazy_local_context`, 29
`dpdispatcher.local_context`, 31
`dpdispatcher.lsf`, 32
`dpdispatcher.machine`, 34
`dpdispatcher.pbs`, 36
`dpdispatcher.shell`, 38
`dpdispatcher.slurm`, 39
`dpdispatcher.ssh_context`, 40
`dpdispatcher.submission`, 42
`dpdispatcher.utils`, 48

`move()` (*dpdispatcher.hdfs_cli.HDFS static method*), 27

N

`NODATA` (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20

O

`OK` (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20
`options` (*dpdispatcher.base_context.BaseContext attribute*), 22
`options` (*dpdispatcher.machine.Machine attribute*), 35

P

`PARAMERR` (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20
`PBS` (*class in dpdispatcher.pbs*), 36
`post()` (*dpdispatcher.dpcloudserver.api.API method*), 20
`PWDERR` (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20

R

`read()` (*dpdispatcher.lazy_local_context.SPRetObj method*), 30
`read()` (*dpdispatcher.local_context.SPRetObj method*), 32
`read_file()` (*dpdispatcher.base_context.BaseContext method*), 22
`read_file()` (*dpdispatcher.dp_cloud_server_context.DpCloudServer method*), 26
`read_file()` (*dpdispatcher.hdfs_context.HDFSContext method*), 29
`read_file()` (*dpdispatcher.lazy_local_context.LazyLocalContext method*), 30
`read_file()` (*dpdispatcher.local_context.LocalContext method*), 32

read_file() (*dpdispatcher.ssh_context.SSHContext method*), 41
read_hdfs_file() (*dpdispatcher.hdfs_cli.HDFS static method*), 28
read_home_file() (*dpdispatcher.dp_cloud_server_context.DpCloudServer method*), 26
readlines() (*dpdispatcher.lazy_local_context.SPRetObj method*), 30
readlines() (*dpdispatcher.local_context.SPRetObj method*), 32
refresh_token() (*dpdispatcher.dpcloudserver.api.API method*), 20
register_job_id() (*dpdispatcher.submission.Job method*), 43
register_task() (*dpdispatcher.submission.Submission method*), 46
register_task_list() (*dpdispatcher.submission.Submission method*), 46
remove() (*dpdispatcher.hdfs_cli.HDFS static method*), 28
REQERR (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20
Resources (*class in dpdispatcher.submission*), 43
resources_arginfo() (*dpdispatcher.machine.Machine class method*), 35
resources_subfields() (*dpdispatcher.lsf.LSF class method*), 33
resources_subfields() (*dpdispatcher.machine.Machine class method*), 35
resources_subfields() (*dpdispatcher.slurm.Slurm class method*), 39
RETCODE (*class in dpdispatcher.dpcloudserver.retcode*), 20
ROLEERR (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20
run_cmd_with_all_output() (*in module dpdispatcher.utils*), 48
run_submission() (*dpdispatcher.submission.Submission method*), 46
running (*dpdispatcher.JobStatus.JobStatus attribute*), 21

S

serialize() (*dpdispatcher.submission.Job method*), 43
serialize() (*dpdispatcher.submission.Resources method*), 44
serialize() (*dpdispatcher.submission.Submission method*), 46
serialize() (*dpdispatcher.submission.Task method*), 48

sftp (*dpdispatcher.ssh_context.SSHContext property*), 41
sftp (*dpdispatcher.ssh_context.SSHSession property*), 42
Shell (*class in dpdispatcher.shell*), 38
Slurm (*class in dpdispatcher.slurm*), 39
SPRetObj (*class in dpdispatcher.lazy_local_context*), 30
SPRetObj (*class in dpdispatcher.local_context*), 32
ssh (*dpdispatcher.ssh_context.SSHContext property*), 41
SSHContext (*class in dpdispatcher.ssh_context*), 40
SSHSession (*class in dpdispatcher.ssh_context*), 41
sub_script_cmd() (*dpdispatcher.lsf.LSF method*), 33
sub_script_cmd() (*dpdispatcher.machine.Machine method*), 35
sub_script_head() (*dpdispatcher.lsf.LSF method*), 33
sub_script_head() (*dpdispatcher.machine.Machine method*), 35
subclasses_dict (*dpdispatcher.base_context.BaseContext attribute*), 22
subclasses_dict (*dpdispatcher.machine.Machine attribute*), 35
Submission (*class in dpdispatcher.submission*), 44
submission_from_json() (*dpdispatcher.submission.Submission class method*), 46
submission_to_json() (*dpdispatcher.submission.Submission method*), 46
submit_job() (*dpdispatcher.submission.Job method*), 43

T

Task (*class in dpdispatcher.submission*), 47
terminated (*dpdispatcher.JobStatus.JobStatus attribute*), 21
THIRDERR (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20
TOKENINVALID (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20
Torque (*class in dpdispatcher.pbs*), 37
try_recover_from_json() (*dpdispatcher.submission.Submission method*), 47

U

UNDERDEBUG (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20
unknown (*dpdispatcher.JobStatus.JobStatus attribute*), 21
UNKNOWNERR (*dpdispatcher.dpcloudserver.retcode.RETCODE attribute*), 20
unsubmitted (*dpdispatcher.JobStatus.JobStatus attribute*), 21
unzip_file() (*in module dpdispatcher.dpcloudserver.zip_file*), 21

```

update_submission_state()           (dpdis-
patcher.submission.Submission     method),
47
upload()      (dpdispatcher.base_context.BaseContext
               method), 23
upload() (dpdispatcher.dp_cloud_server_context.DpCloudServerContext
          method), 27
upload() (dpdispatcher.dpcloudserver.api.API method),
20
upload() (dpdispatcher.hdfs_context.HDFSContext
          method), 29
upload() (dpdispatcher.lazy_local_context.LazyLocalContext
          method), 30
upload() (dpdispatcher.local_context.LocalContext
          method), 32
upload() (dpdispatcher.ssh_context.SSHContext
          method), 41
upload_() (dpdispatcher.local_context.LocalContext
          method), 32
upload_jobs() (dpdispatcher.submission.Submission
               method), 47
USERERR(dpdispatcher.dpcloudserver.retcodes.RETCODE
        attribute), 20

```

V

VERIFYERR (dpdispatcher.dpcloudserver.retcodes.RETCODE
attribute), 20

W

waiting (dpdispatcher.JobStatus.JobStatus attribute), 21
write_file() (dpdispatcher.base_context.BaseContext
method), 23
write_file() (dpdispatcher.dp_cloud_server_context.DpCloudServerContext
method), 27
write_file() (dpdispatcher.hdfs_context.HDFSContext
method), 29
write_file() (dpdispatcher.lazy_local_context.LazyLocalContext
method), 30
write_file() (dpdispatcher.local_context.LocalContext
method), 32
write_file() (dpdispatcher.ssh_context.SSHContext
method), 41
write_home_file() (dpdis-
patcher.dp_cloud_server_context.DpCloudServerContext
method), 27
write_local_file() (dpdis-
patcher.dp_cloud_server_context.DpCloudServerContext
method), 27

Z

zip_file_list() (in module dpdis-
patcher.dpcloudserver.zip_file), 21